

## CLAIMS:

- 5 1. A gas deflector for use with a cylindrical gas generator, the gas deflector comprising a generally tubular housing, to accommodate the cylindrical gas generator, the housing having two terminal portions of generally circular cross-section and having an intermediate region provided with an outwardly extending formation, the outwardly extending formation defining, at either end  
10 thereof, an opening through which gas may flow in a direction substantially parallel to the axis of the housing.
2. A gas deflector according to Claim 1 wherein the gas deflector is provided with a mounting stud.
- 15 3. A gas deflector according to Claim 1 or Claim 2 wherein part of one end region of the housing is cutaway to receive a mounting stud on a gas generator.
4. A gas deflector according to any one of the preceding Claims wherein  
20 one of the gas outlet openings defined by the outwardly extending formation is of a greater cross-sectional area than the other of the openings formed by the formation.
5. A gas deflector according to any one of the preceding Claims wherein  
25 the formation is a formation which extends radially outwardly in a bridge-like manner.
6. A gas generator according to Claim 4 wherein the outwardly extending formation has a first portion and a section portion, the first portion having a

greater radial extent than the second portion and thus defining the aperture of greater cross-sectional area.

7. A gas generator according to any one of Claims 4 to 6 wherein the formation has an inclined outer wall, thus being of substantially tapering form, one end of the formation defining the said relatively large cross-section aperture and the other end defining the relatively small cross-section aperture.

8. A gas deflector according to any one of the preceding Claims in combination with a cylindrical gas generator received within the gas deflector, the cylindrical gas generator having at least one gas outlet aperture formed in the side wall thereof in a region aligned with the said formation, the gas generator having an external diameter substantially equal to the internal diameter of the terminal regions of the deflector.

15

9. A gas deflector and gas generator combination according to Claim 8 as dependent upon Claim 3 in which the gas generator is provided with a mounting stud, the mounting stud being received within said cut-away region of the gas deflector housing.

20

10. An air-bag incorporating a gas deflector and gas generator combination according to Claims 8 or 9 wherein the air-bag defines two internal chambers, one of said openings communicating with one of the chambers and the other of the openings communicating with the other of the chambers.

25

11. An air-bag according to Claim 10 wherein part of the air-bag is clamped to the exterior of the gas generator so that the chambers are substantially sealed from each other.